



Tender specification

DA-S 20-130/T-EN54

**Aluminium Sound projector, 20 W, 100 V, certified according EN 54-24,
compliant BS 5839**

Soundprojector, waterproofed 130 mm full-range speaker, 100 V, equipped with ceramic block and thermal fuse.

Powder-coated aluminium-housing

Available in all RAL-colours.

IP65 protection standard, weatherproof, corrosion-resistant.

Installation via a corrosion-resistant V4A mounting-bracket.

Provided with a 1 m, five-pin cable. Not included in the delivery:

Cable gland for the signal cable from the amplifier.

RoHS-compliant.

Technical Specifications:

Rated voice/noise power 100 V (Watt):	20/15/10/5
Low ohm connection (Ohm):	-
Dimensions (mm):	∅ 183x150
Weight (kg):	2,52
Colour:	RAL 9010
Frequency range (Hz):	800 - 16.700
Frequency response IEC268-5 (-10dB) (Hz):	150 - 20.000
SPL IEC268-5, 1 W/1 m (dB):	103,2
SPL IEC268-5, 1 W/4 m (dB):	91,2
SPL IEC268-5, Pmax./4 m (dB):	104,2
Sensitivity EN54-24, 1 W/4 m (dB):	80,3
Dispersion angle-6 dB, 500 Hz:	360°
Dispersion angle-6 dB, 1 kHz:	210°
Dispersion angle-6 dB, 2 kHz:	105°
Dispersion angle-6 dB, 4 kHz:	55°