



Tender specification

DA 10-260/T-EN54

**Aluminum sound projector, 10 Watt, 100 Volt, certified according to EN 54-24,
BS 5839 compliant**

10W bi-directional sound projector with two 130mm full range speakers, aluminum housing, built-in ceramic black and thermal fuse, waterproofed chassis.

Can be painted in any other RAL color.

IP66 certified.

Mouting by screws to the vandal-proof foot of the speaker.

RoHS compliant.

Technical Specifications:

Rated voice/noise power 100 V (Watt):	10/6/3/1,5
Low ohm connection (Ohm):	-
Dimensions (mm):	∅ 166x197x161
Weight (kg):	2,35
Colour:	RAL 9010
Frequency range (Hz):	237 - 12.400
Frequency response IEC268-5 (-10dB) (Hz):	79 - 17.500
SPL IEC268-5, 1 W/1 m (dB):	95,3
SPL IEC268-5, 1 W/4 m (dB):	83,3
SPL IEC268-5, Pmax./4 m (dB):	93,3
Sensitivity EN54-24, 1 W/4 m (dB):	77,6
Dispersion angle-6 dB, 500 Hz:	130°
Dispersion angle-6 dB, 1 kHz:	150°
Dispersion angle-6 dB, 2 kHz:	145°
Dispersion angle-6 dB, 4 kHz:	75°